

WET LOOK



Protector for Concrete Pavers Gloss Finish



(141-013 / 3.78 L – 141-016 / 18.93 L)

UPDATE

December 8, 2015

Make sure that you have an up-to-date technical data sheet in hand by consulting our Web site: techniseal.com
U.S.A. and Canada: dial 1 800 465-7325
Others: dial (514) 523-8324 (Canada)

APPLICATIONS

- Recommended for driveways, walkways and patios

PROPERTIES

- Enhances the colour of pavers
- Ideal for driveways, parking lots, walkways and patios
- Single-coat application - Covers up to 14 m² (150 sq. ft.)

DESCRIPTION

Made of acrylic and plasticizers, Wet Look WL1-2 Protector is specially designed to protect concrete pavers. Formulated both for bare and previously sealed surfaces, it prevents deterioration due to chemical products such as de-icing salts, while providing resistance to acids and alkalis. Its transparent film stops the penetration of contaminants, facilitating the maintenance of pavers.

DIRECTIONS

BEFORE YOU BEGIN

- Do not apply to natural stone or to wet-cast pavers, stamped or poured concrete. • Apply only to bare material*, or to material previously sealed with this product or with Techniseal[®] Wet Look WL1 or WL2 (141-123 or 141-103). Wait until the Protector is worn before recoating the surface (minimum 2 years). • With the appropriate Techniseal[®] stripper, remove any unknown coating that was previously applied. • Wear adequate protective clothing and an approved respirator. • **ALWAYS TEST** on a small hidden area of approximately 0.4 m² (4 sq. ft.) to ensure that result meets your expectations (see Warranty).

*ABSORPTION TEST: Sprinkle a few drops of water on surface. If water is absorbed, move on to the next point. If water is repelled, do not apply this product.

SURFACE PREPARATION (ESSENTIAL)

1. Cover vegetation, vehicles and adjacent surfaces that are not to be treated.
2. Remove stains with the appropriate Techniseal® stain removers.
3. Prepare the entire surface with Techniseal® Pre-Seal Cleaner (141-534), as directed on product label.

APPLICATION

Application Conditions:

- Surface must be clean, dry and warm to the touch.
- Temperature must be between 10°C and 30°C.
- No rain forecasted for the next 24 hours.
- Sprinkler system must be turned off.
- Use a consistent application method over entire surface.

Necessary Tools:

- Techniseal® Slit-Foam Roller (145-930), and solvent-resistant paint tray
- Low-pressure airless sprayer (< 50 psi) or solvent-resistant pump sprayer (optional)

Do not dilute. Shake well or stir product before and during application.

Sprayer Application (Best Practice): Work in sections of no more than 4.6 m² (50 sq. ft.). **Saturate** a section with a coat of Protector. With the roller, remove excess on the surface before it dries. Repeat for subsequent sections, maintaining a wet edge in order to prevent overlap marks.

Roller Application: **Saturate** the surface with a coat of Protector, avoiding accumulation of excess product. Maintain a wet edge in order to prevent overlap marks.

Second Coat (Never Sealed Surfaces Only): Once the surface is dry to the touch (+/- 4 hours), apply a second coat following the same method as before.

Traffic: Pedestrian: 24 h. / Vehicular: 48 to 72 h. Block access during that period.

CAUTION

- Any new concrete product has the potential to produce efflorescence (whitish salts) on its surface. This Protector, like any film-forming coating, carries a small risk of trapping efflorescence beneath its film. Consult the paver manufacturer or visit techniseal.com for more information.
- Do not attempt sprayer application on windy days.
- Do not apply this product over a blotchy or hazed surface.
- This product will make the surface more slippery when wet. If slipping is a problem, consider Techniseal® Colour Boost CB Protector (141-393).
- An over-accumulation of product could lead to surface whitening.
- Extreme climate or heavy traffic could limit product longevity.

COVERAGE

3.78 L cover up to 14 m² (150 sq. ft.) for the first coat. The second coat should cover up to 19 m² (200 pi²) per 3.78 L.

STORAGE

Store in a cool, dry place.

CLEANING & DISPOSAL

Wash tools with lacquer thinner. Consult your retailer or municipality regarding the disposal of empty containers or unused product.

PACKAGING

Product code	Retail Size	Units per box	Units per pallet
141-013	3.78 L	4	180
141-016	18.93 L	–	36

WARNING

CONTENTS MAY CATCH FIRE. CONTENTS HARMFUL. MAY IRRITATE EYES. MAY IRRITATE SKIN. Do not smoke. Do not swallow. Do not get in eyes. Do not get on skin or clothing. Use only in a well-ventilated area. Keep away from flames, such as a pilot light, and any object that sparks, such as an electric motor. **KEEP OUT OF REACH OF CHILDREN.** Wear protective gloves and eye/face protection. **FIRST AID TREATMENT Contains:** Acetone; Solvent naphtha (petroleum), light arom; 1,2,4-trimethylbenzene. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 15 minutes. If on skin, rinse well with water.

Coating Category: Low Solids Coating (VOC Concentration Limit : 120g/L)

SHIPPING

Land and sea

UN1993

Flammable liquids, n. o.s. (Acétone)

Class: 3

PG: II

LIMITED WARRANTY

Having no control over the use of the products, Techniseal® does not guarantee finished work. Replacement of any defective product shall be the buyer's sole remedy under this warranty. A proof of purchase will be required for any claim. Before using this product, user shall determine the suitability of the product for its intended use, and user alone assumes all risks and liability whatsoever in connection therewith. User shall test product in a small inconspicuous area (approx. 0.4 m² – 4 sq. ft.) under projected conditions of use. In the event that no test was carried out, the warranty will only apply to 0.4 m² (4 sq. ft.). This limited warranty excludes any liability for any consequential, incidental, indirect or special damages. Except for the limited warranty described above, manufacturer specifically disclaims and excludes any other express warranty, any implied warranty of merchantability of goods, and implied warranty of fitness of goods for any particular purpose.