



PAVER RESTORER

(60200243/ 4 L)

UPDATE

March 29, 2018

Make sure that you have an up-to-date technical data sheet in hand by consulting our website: techniseal.com
Canada and U.S.A.: dial 1 800 465-7325
Others: dial (514) 523-8324 (Canada)

APPLICATIONS

- Tiles and pavers made of concrete or clay

PROPERTIES

- Removes cement and mortar jointing haze
- Removes stains generated by paver and slab cuts

DESCRIPTION

Techniseal® Paver Restorer removes the haze left after grout and masonry work on tiles and pavers made of concrete or clay. It works efficiently without discolouring or damaging the surface. Unlike muriatic acid, Techniseal® Paver Restorer releases very little odour and is environmentally friendly.

DIRECTIONS

BEFORE YOU BEGIN

- Do not use on natural stone, wet-cast pavers and stamped or poured concrete.
- Wear rubber gloves and safety goggles.
- **ALWAYS TEST** on a small hidden area of approximately 4 sq. ft. to ensure that result meets your expectations
- Never use this product without first consulting with local authorities regarding the application of such products, waste management and run-offs.
- Do not apply under blazing sun.
- Protect people, vehicles, property, vegetation, and other surfaces not set for cleaning from product, residue, splash, fumes and wind drift.

PREPARATION

SURFACE WETTING: To reduce the penetration of Paver Restorer into sand joints and thus make product easier to rinse, first wet the surface to saturate joints with water; then let the surface dry, and apply product.

DILUTION: Dilution must be adjusted according to the amount of haze present on the pavers. In a plastic container, dilute the product in water. Always pour the product in water, not the other way around. The recommended dilution ratio is 1 part product in 1 to 4 parts water, depending on the severity of the haze. Always test the dilution on a small area first, in order to clean the surface without damaging or discoloring the material. If haze persists, reapply product using the proper dilution.

Newly installed polymeric sand: Wait at least 30 days before applying the product.

APPLICATION

Important: Do not apply product with a mop or a broom. Never let the cleaning solution dry on the surface; keep it wet at all times until it is completely rinsed off. **Never** apply the product at full strength.

Clean one section of 200 sq. ft. at a time. On each section, starting from the bottom of the slope, cover surface with diluted solution, making sure to cover the whole section without leaving any dry spots. Next, gently scrub the surface using a street broom; rinse immediately and thoroughly, until all traces of foam disappear, before proceeding to another section. In cleaning each section, overlap the edges of adjoining sections to ensure that no uncleaned strips are left between them. Once all the sections have been cleaned, rinse thoroughly and let dry. If there is any haze left on the surface, repeat cleaning.

COVERAGE

4 L of product clean up to 19 m² (200 sq. ft.). The coverage will depend on the severity of the haze.

STORAGE

Store in a cool and dry place, away from the sunlight and with adequate ventilation.

PACKAGING

Product code	Size	Units per box	Units per pallet
60200243 (241-604)	4 L	4	144

WARNING

CONTENTS MAY BE HARMFUL. **MAY IRRITATE EYES. MAY IRRITATE SKIN.** Do not swallow. Do not get in eyes. Do not get on skin or clothing. **KEEP OUT OF REACH OF CHILDREN.** Wear protective gloves and eye/face protection. **FIRST AID TREATMENT Contains:** urea hydrochloride. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 15 minutes. If on skin, rinse well with water.

EMERGENCY PHONE: CANUTEC (613) 996-6666. SEE MATERIAL SAFETY DATA SHEET FOR THIS PRODUCT.

SHIPPING

Land

Can be transported in limited quantity

Sea

UN3265

Corrosive liquid, acidic, organic, n.o.s. (urea hydrochloride)

CLASS: 8

PG: III

LIMITED WARRANTY

Techniseal® warranties this product against manufacturing defects. As Techniseal® has no control over surface preparation and product application, results cannot be guaranteed. The Techniseal® warranty is limited only to the replacement of a product proven to be defective, and will never cover the cost of labour. A proof of purchase will be required for any claim. Notice : User should make sure that this product meets their needs by carrying out a test under anticipated conditions of use on a 0.4 m² (4 sq.ft.) area. In the event that no test was carried out, the warranty will only apply to 0.4 m² (4 sq.ft.).