



PROFESSIONAL GRADE OIL & GREASE REMOVER for PAVERS

(70975913 / 950 ml)

UPDATE

March 29, 2018

Make sure that you have an up-to-date technical data sheet in hand by consulting our website: techniseal.com
Canada and U.S.A.: dial 1 800 465-7325
Others: dial (514) 523-8324 (Canada)

APPLICATIONS

- For concrete pavers and slabs

PROPERTIES

- Removes penetrated petroleum-based products
- Clean - dries from a liquid to a powder

DESCRIPTION

Techniseal® Professional-Grade Oil & Grease Remover is an industrial-strength oil and grease remover that lifts and absorbs embedded oil and grease stains as it dries from a liquid to a powder. It is specially formulated for concrete pavers and slabs, poured or stamped concrete, etc. Easy to use, Techniseal® Professional-Grade Oil & Grease Remover works without damaging or discolouring the material.

DIRECTIONS

Important: Wear adequate protective clothing. **ALWAYS TEST** on a small hidden stain to ensure the results will meet your expectations. **Do not use on asphalt.** For best results, use when temperature is between 15°C and 25°C, and provide maximum ventilation. During hot summer days, apply product in the evening and let work overnight.

APPLICATION

Shake well. Apply a generous amount of product to an oil or grease stain and let sit until product has turned to powder. With temperature above 15°C and good ventilation, this process should take between 5 and 8 hours. Process is slowed down and may be stopped at lower temperatures. When the product has completely dried to a powder, sweep up with a broom and dispose of the powder.

Note: Surface may still appear dark immediately after powder has been swept up. This is not oil but rather a citrus-based solvent that should evaporate within a few hours or days. **Note:** This product dissolves sealants.

PACKAGING

Product code	Size	Units per box	Units per pallet
70975913 (241-591)	950 ml	6	600

WARNING

CAUSES BURNS. DANGEROUS FUMES FORM WHEN MIXED WITH OTHER PRODUCTS. Do not mix with Acid. Do not swallow. Do not get in eyes. Do not get on skin or clothing. Do not breathe fumes. Use only in a well-ventilated area. Keep away from flames or sparks. Handle with care. **KEEP OUT OF REACH OF CHILDREN.** Wear protective gloves and eye/face protection: Chemical splash goggles or face shield. Use chemical-resistant, impervious gloves. Wear appropriate respirator when ventilation is inadequate. **FIRST AID TREATMENT Contains:** Proprietary Chelating Agents; (R)-p-mentha-1,8-diene. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 15 minutes. If on skin, rinse well with water. If on clothes, remove clothes. If breathed in, move person to fresh air.

EMERGENCY PHONE: CANUTEC (613) 996-6666. SEE MATERIAL SAFETY DATA SHEET FOR THIS PRODUCT.

SHIPPING

Land

Transported in limited quantity

Sea

UN1993

Flammable liquids, n.o.s. (D-Limonene)

Class: 3

PG: III

LIMITED WARRANTY

Manufacturer's liability is limited to the replacement of the product. A proof of purchase will be required for any claim.