



Crack Filler for Concrete



(70978057 / 300 ml)

UPDATE

May 1, 2018

Make sure that you have an up-to-date technical data sheet in hand by consulting our Web site: techniseal.com

Canada and U.S.A.: dial 1 800 465-7325

Others: dial (514) 523-8324 (Canada)

APPLICATIONS

- Floors, walls, sidewalks, steps, pool decks, roughcast, mortar, etc.

PROPERTIES

- Ideal for floors, walls, sidewalks, steps, roughcast, mortar, etc.
- Fills cracks 0.5 to 1 cm wide
- Granular texture
- Dries quickly, very durable

DESCRIPTION

Flexible and very durable, Techniseal[®] Crack Filler for Concrete is an acrylic compound specially designed to repair concrete floors, mortar joints, sidewalks, steps, pool decks, roughcast and any other concrete or masonry surface. Its texture and colour perfectly blend with surfaces. Since it is paintable, it is ideal for repairs done prior to the application of a coating. Easy to apply, Techniseal[®] Crack Filler for Concrete dries quickly, strongly adheres to inner walls of cracks and perfectly resists the elements. Water-based and containing very little solvent (V.O.C.: 43.43 g/L), it is environmentally friendly and free of unpleasant fumes.

Note: This product is formulated for cracks 1 cm (1/2") wide or less.

DIRECTIONS

Surface should be clean and dry. Temperature should be above 5°C. Applying steady pressure, fill cracks to surface level; smooth if desired. Let dry completely (for at least 24 hours) before applying a coating or driving on the surface. Cleaning of tools: Wash with water before product dries.

Note: Do not apply if rain or frost is forecasted within 12 hours. Store at a temperature above 15°C.

CAUTION

MAY IRRITATE EYES. Do not get in eyes. Do not get on skin or clothing. **KEEP OUT OF REACH OF CHILDREN. USE ENTIRE CONTENTS ON OPENING. This container is not child-resistant once opened. FIRST AID TREATMENT**
Contains: Stoddard solvent; Ethanediol. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 15 minutes. If on skin, rinse well with water.

PACKAGING

Product code	Retail Size	Units per box	Units per pallet
70978057 (149-781)	304 ml	12	1296

SHIPPING

Land and sea

NOT REGULATED

LIMITED WARRANTY

Techniseal® warrants this Protector against manufacturing defects. As Techniseal® has no control over surface preparation and product application, results cannot be guaranteed. The Techniseal® warranty is limited only to the replacement of a product proven to be defective, and will never cover the cost of labour. A proof of purchase will be required for any claim. Notice : User should make sure that this product meets their needs by carrying out a test under anticipated conditions of use on a 4 sq.ft. (0.4 m²) area. In the event that no test was carried out, the warranty will only apply to 4 sq.ft. (0.4 m²).