



BORDERBOND™ Fortifier for Border Pavers

UPDATE

April 23, 2018

Make sure that you have an up-to-date technical data sheet in hand by consulting our website: techniseal.com
U.S.A. and Canada: dial 1 800 465-7325
Others: dial (514) 523-8324 (Canada)

APPLICATIONS

- Residential driveways, sidewalks, pool decks, patios, courtyards, garage floors
- Commercial and light industrial driveways, sidewalks, walkways, courtyards

PROPERTIES

- Easy to use – Straight from the bottle
- Easily mixes with DriBond
- Maximizes bond strength of DriBond

DESCRIPTION

BorderBond is a ready-to-use liquid fortifier that mixes with DriBond to bond border pavers firmly to the concrete base.

DIRECTIONS

BEFORE YOU BEGIN

Before proceeding with the installation, make sure you have an up-to-date technical data sheet in hand and visit techniseal.com to watch the application video. **ALWAYS TEST** on a small hidden area of approximately 4 sq. ft. to ensure that result meets your expectations (see Warranty).

Necessary tools:

- Shovel or garden hoe
- Mixing whip and drill (optional)
- Wheelbarrow or any suitable mixing container
- 1/2" x 1/2" square notch trowel or margin trowel

PREPARATION

Shake container well before use. Do not dilute. Mix one bag of DriBond with one container of BorderBond. To obtain a more uniform consistency, it is recommended to mix both products gradually, in two or more doses. Mix must have a smooth, creamy consistency.

APPLICATION

1. Remove any dry DriBond from the border areas. Surface must be clean and dry.
2. Using a 1/2" x 1/2" square notch trowel or a margin trowel, apply mix to the borders and transitions as necessary. This will create a mortar bed on which to lay the pavers.
3. Install border pavers as described on the DriBond bag or technical data sheet.
4. Remove any excess product from the edge of the finished paved area. There should be **no air pockets or voids** under the border pavers. **Never** allow the border pavers to protrude past the edge of the existing concrete.

Note: Although not mandatory, wetting the concrete surface prior to applying the BorderBond mix will insure optimal bond strength and adhesion.

CLEANING

Clean tools and hands with warm water.

COVERAGE

1.58 gal of BorderBond mixed with one bag of DriBond cover approximately 30 linear feet, based on a 12" wide border. Coverage will depend on surface condition and desired BorderBond bedding thickness.

Approximate Coverage Chart for a 1.58 gal of BorderBond:

Border Width	Coverage in linear feet
4"	90 to 120
6"	60 to 70
9"	40 to 45
12"	30 to 35

SHELF LIFE AND STORAGE

2 years when kept in an unopened container and stored in a cool and dry place, away from the sunlight and with adequate ventilation. For an opened container, shelf life is approximately 2 hours.

SAFETY WARNINGS

KEEP OUT OF THE REACH OF CHILDREN. FIRST AID Eye contact: Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention if symptoms occur. **Skin contact:** Wash contaminated skin with soap and water. Get medical attention if symptoms occur. **Inhalation:** Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention if symptoms occur. **Ingestion:** Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention if symptoms occur.

SHIPPING

LAND & SEA:
Not regulated

PACKAGING

BorderBond	Product Code	Color	Retail Size	Units per Box	Boxes per Pallet
	60050792 (221-B05)	N/A	1.58 gal.	2	36

LIMITED WARRANTY

Manufacturer, having no control over the use of the materials, does not guarantee finished work. Replacement of any defective product shall be the buyers sole remedy under this warranty. A proof of purchase will be required for any claim. Before using this product, user shall determine the suitability of the product for its intended use and user alone assumes all risks and liability whatsoever in connection therewith. User shall test product in a small inconspicuous area (approx. 4 sq. ft.) under projected conditions of use. In the event that no test was carried out, the warranty will only apply to 4 sq.ft. This limited warranty excludes any liability for any consequential, incidental, indirect or special damages. Except for the limited warranty made above, manufacturer specifically disclaims and excludes any other express warranty, any implied warranty of merchantability of goods and implied warranty of fitness of goods for any particular purpose.