



## PROTECTOR for WET-CAST PAVERS (WC)

NATURAL LOOK - MATTE FINISH - WATER BASED

(60301539/1 gal.)

(60301871/5 gal.)

### UPDATE

---

April 23, 2018

Make sure that you have an up-to-date technical data sheet in hand by consulting our Web site: [techniseal.com](http://techniseal.com)  
U.S.A. and Canada: dial 1 800 465-7325  
Others: dial (514) 523-8324 (Canada)

### APPLICATIONS

---

- Pool decks, patios, walkways and driveways made of wet-cast pavers.

### PROPERTIES

---

- Preserves the natural look of wet-cast pavers
- Ideal for slip-prone surfaces
- Stain guard - repels contaminants
- Water based

### DESCRIPTION

---

Made of water- and oil-repellent agents, WC Protector for Wet-Cast Pavers is specially formulated for the treatment of wet-cast concrete products\*. It prevents deterioration due to chemical products such as de-icing salts, while providing resistance to acids and alkalis. Its active agents form an invisible bond that stops the penetration of contaminants, facilitating the maintenance of wet-cast pavers and slabs. Water based, this Protector does not release unpleasant fumes, and is environmentally friendly.

\* Important: Contact the paver manufacturer or distributor to find out if pavers to be treated are truly wet-cast pavers.

### DIRECTIONS

---

#### BEFORE YOU BEGIN

- Do not apply to natural stone as well as stamped or poured concrete. • Apply only to bare material\* or to material previously sealed with this product. Wait until surface is no longer water-repellent before recoating (minimum 2 years).
- With the appropriate Techniseal® stripper, remove any unknown coating that was previously applied.
- **ALWAYS TEST** on a small hidden area of approximately 4 sq. ft. to ensure that result meets your expectations (see Warranty).

\*ABSORPTION TEST: Sprinkle a few drops of water on surface. If water is absorbed, move on to the next point. If water is repelled, do not apply this product and contact Techniseal Technical Service.

**SURFACE PREPARATION (ESSENTIAL)**

1. Some wet-cast pavers are very sensitive to cleaning products; **ALWAYS TEST** on a small area to ensure pavers are compatible with cleaner.
2. Cover vegetation, vehicles and adjacent surfaces that are not to be treated.
3. Remove stains with the appropriate Techniseal® stain removers.
4. Prepare the entire surface with Techniseal® Wet-Cast Paver Prep, as directed on product label

**APPLICATION**

**Application Conditions:**

- Surface must be clean, dry and warm to the touch.
- Temperature must be between 50°F and 85°F.
- No rain forecasted for the next 24 hours.
- Sprinkler system must be turned off.
- Use a consistent application method over entire surface.

**Necessary Tools:**

- 3/8” or 1/2” polyester nap roller and paint tray
- Low-pressure airless sprayer (< 50 psi) or pump sprayer (optional)

Do not dilute. Shake well or stir product before and during application. Work in sections of no more than 100 sq. ft. Apply in such a way that you can return to each section without walking on fresh Protector (2 coats wet-on-wet technique).

**Sprayer Application (Best Practice): Saturate** the surface with a first coat of Protector. Remove excess with the roller. Immediately upon completion of a section, apply a second coat following the same method. Repeat for subsequent sections, maintaining a wet edge in order to prevent overlap marks. Once again, remove excess product with a dry roller, before it dries. An over-accumulation of product could make dust stick to the surface. It could also make surface more slippery.

**Roller Application: Saturate** the surface with a first coat of Protector, avoiding accumulation of excess product. Immediately upon completion of a section, apply a second coat following the same method. Maintain a wet edge in order to prevent overlap marks.

**Traffic:** Pedestrian: 24 h. / Vehicular: 48 to 72 h. Block access during that period.

**CAUTION**

- Do not attempt sprayer application on windy days.
- Do not apply this product over a blotchy or hazed surface.
- Do not apply with a foam roller.

**COVERAGE**

1 gal. covers up to 120 sq. / 5 gal. cover up to 600 sq. ft. Coverage will depend on joint width and surface porosity.

**STORAGE**

Keep from freezing. Store in a cool, dry place.

**CLEANING & DISPOSAL**

Wash tools and hands with warm soapy water. Consult your retailer or municipality regarding the disposal of empty containers or unused product.

**PACKAGING**

Product code	Size	Units per box	Units per pallet
60301539 (121-163)	1 gal.	2	180
60301871 (121-166)	5 gal.	—	—

## WARNING

---

### PROTECTOR for WET-CAST PAVERS - WC

Read label before use. KEEP OUT OF THE REACH OF CHILDREN. If medical advice is needed, have product container or label at hand.

Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 5.4%

**Coating Category:** Waterproofing Concrete/ Masonry Sealers (VOC Concentration Limit: 100g/L)

**EMERGENCY PHONE: CANUTEC (613) 996-6666. SEE MATERIAL SAFETY DATA SHEET FOR THIS PRODUCT**

Techniseal®, 300 Liberté, Candiac (Québec), Canada J5R 6X1

## SHIPPING

---

### Land and sea

NOT REGULATED

## LIMITED WARRANTY

---

Having no control over the use of the products, Techniseal® does not guarantee finished work. Replacement of any defective product shall be the buyer's sole remedy under this warranty. A proof of purchase will be required for any claim. Before using this product, user shall determine the suitability of the product for its intended use, and user alone assumes all risks and liability whatsoever in connection therewith. User shall test product in a small inconspicuous area (approx. 4 sq. ft.) under projected conditions of use. In the event that no test was carried out, the warranty will only apply to 4 sq. ft. This limited warranty excludes any liability for any consequential, incidental, indirect or special damages. Except for the limited warranty described above, manufacturer specifically disclaims and excludes any other express warranty, any implied warranty of merchantability of goods, and implied warranty of fitness of goods for any particular purpose.